FUJICA AX-1, AX-3, AX-5

(system accessories)

This camera manual library is for reference and historical purposes, all rights reserved.

This page is copyright by **mike@butkus.org**, M. Butkus, NJ.

This page may not be sold or distributed without the expressed permission of the producer

On-line camera manual library

www.butkus.us

SYSTEM ACCESSORIES

Your Fujica AX-1/AX-3/AX-5 has a complete assortment of "system accessories" designed to expand the camera's scope and increase the fun of picture taking.

FUJICA AUTO WINDER X



This compact, lightweight unit is attached to the bottom of your camera to wind the film automatically at a rate of two frames per second so that you can concentrate on your subject and won't miss those decisive moments that can easily be lost forever. It will advance the film continuously while the shutter release is depressed or one frame at a time each time the shutter is tripped. It operates on four penlight batteries and a red LED will turn on while the film is advancing.

FUJICA PHOTO RECORDER



This data back is interchangeable with the Camera Back and is equipped with a hand-writing pen that is inter linked with a "light pen" for printing in data (up to about 30 letters) in the bottom left corner of the picture. The Camera Back can be easily detached by pushing down the hinge pin.

FUJICA RIGHT ANGLE FINDER



An accessory for simplifying viewing when the camera must be held low to the floor or when it is attached to a copying board. It is provided with an eyesight adjustment lens.

FUJICA AUTO EXTENSION TUBE



They are used for taking ultra close-ups and have a tube length of 25mm and 50mm. Combined with a normal lens, the X25 unit provides 1/2-actual-size, and the X50 unit life size, pictures. Exposure setting is easy because it offers full aperture metering and automatic stop down.

FUJICA AUTO BELLOWS X



Designed for taking ultra-close-ups, it provides 1-3X magnification in combination with a 50mm normal lens. It is equipped with an automatic diaphragm to allow you to focus with the aperture wide open. Convenience accessories include a focusing rail and a slide copier.



This is used in combination with the Fujica Auto Bellows ${\tt X}$ to permit simple, accurate focusing.



Attached to the front end of the Fujica Focusing Rail X, this copier simplifies copying of color and black and white slides as well as roll-film pictures.

FUJICA CLOSE-UP LENS

Attached to a F 1.6 50mm normal lens, it lets you take close-ups of subjects about 32 to 48cm away from the camera lens.



This accessory Is used for copying pictures taken on 8 and 16mm films.

FUJICA MICROSCOPE ADAPTER X



This is used to couple the camera to a microscope to take photomicrographs.

FUJICA REVERSE ADAPTER X



It lets you mount the lens in reverse to take closeups. Larger-than-life close-ups will turn out sharper when the lens is mounted in reverse on an extension bellows with this adapter, www.butkus.org

FUJICA TELECONVERTER 2X



Mounted between the lens and camera body, it will double the focal length of your lens to take telephoto pictures.

SYSTEM ACCESSORIES

FUJICA FILTERS (12 types) Filter	Film type	Uses		
SKYLIGHT (1B)	Black and White,	Reduces the blue-greenishness in landscape picture. Used also for lens protection.		
UV	Black and white, color	Ultraviolet absorbing filter. Used also for lens protection.		
SY48	Black and white	Yellow filter. For landscapes.		
S056	Black and white	Orange filter. For pictures of mountains and distant landscapes.		
SR60	Black and white Red filter.	For strong contrast and infrared pictures.		
ND4X	Black and white color	Gray filter. For reducing the light intensity.		
LBA-12	Color	Color conversion filter for tungsten film.		
LBB-12	Color	conversion filter for daylight film.		
FL-W	Color	Light balancing filter for shooting in fluorescent light.		
PL	Black and white, color	Removal of reflections.		
CROSS4	Black and white, color	For special effects. Contains a cross screen.		
MULTI-5	Black and white, color	For special effects. Yields multiple images (5) on the same frame.		